

An USB removable memory with replaceable storage medium for optional upgrade
and extension of the storage capacity

Technical Field

5 The present invention relates to a removable memory using USB connector, particularly to an USB removable memory with replaceable storage medium for optional upgrade and extension of the storage capacity.

Prior Art

10 USB (Universal Serial Bus) technology is a newer kind of interface technology which is widely used in the field of PC in recent years step by step. USB technology consists of three parts: PC system with USB interface, system software supporting USB, and device using USB interface. "Universal Serial Bus" (USB 2.0) is a specification for connection of computer peripheral, which is worked out
15 by some big PC enterprises including Compag, HP, Intel, Lucent, Microsoft, NEC and Philips. USB 1.1 specification is now generally adopted, whose speed is 100 times faster than that of standard serial port, and which supports simultaneous connection of multi-device and possesses real "plug-and-play" feature. Now, USB is accepted gladly by peripheral manufacturers due to these advantages.

20 On the other hand, the FLASH (flash memory) as a nonvolatile storage medium has much higher performance in respect of data stability and adaptability of environment than magnetic storage medium, and has distinctly overcome the disadvantages of complex mechanism and small storage capacity of the floppy drive and floppy disk. Therefore, while the production cost of semiconductor is reduced,
25 the removable memory using USB interface technology and flash memory technology is widely applied. Such products in the prior art include the following parts: USB interface, controller, flash memory unit. The controller is electrically

connected to the USB interface and the flash memory. Such product is provided with a housing, in which the flash memory and the controller are fixedly placed. The USB interface protrudes from the housing. As a end product, the capacity of such product is fixed. It is necessary to buy a completed USB memory when
5 a memory with larger capacity is needed. On the other hand, the completed USB memory must be throw away if the flash memory or the controller has any problem. As a result, a variety of requirements cannot be satisfied, and wasting is done.

Summary of the Invention

10 The object of the present invention is to provide a USB removable memory with replaceable storage medium for optional upgrade and extension of the storage capacity, wherein the flash memory part can be physically separated from the controller and the USB interface connected with the controller, and the flash memory part can be conveniently plugged/unplugged onto/from the memory body.

15 Another object of the present invention is to provide a USB removable memory with replaceable storage medium for optional upgrade and extension of the storage capacity, wherein the controller can be neatly connected to other device needed to connect with a computer by USB port.

The above-mentioned objects are achieved through the following technical
20 solution:

An USB removable memory with replaceable storage medium for optional upgrade and extension of the storage capacity, including an USB connector, a controller and a flash memory; wherein, the USB connector and the controller are integrated as a memory body; the flash memory as the physically-independent storage
25 component is attached to the body, and is electrically connected to the controller; said body is provided with write/read status control switch.

Said flash memory part is mounted on the body by means of guide channel,

and the electrical connection between them is elastic tip-touch connection. Certainly, the electrical connection between the flash memory part and the body may be the plug-in connection or elastic fastener connection.

In addition, a dismountable back cover is provided in the rear of the housing
5 of the body. The body is provided with a chamber for flash memory part, a flash memory is placed in the chamber.

furthermore, the electrical connection between said flash memory part and said body is achieved by means of universal interface, such as USB interface or SMMC.

10 The back cover can be mounted on the body by means of guide channel or clasp according to the requirement.

The present invention possesses following obvious advantages in comparison with the prior art.

The memory can be optionally upgraded and extended in its storage capacity,
15 so it is convenient for user, the cost is reduced, and the resource is saved.

The flash memory as independent spare part is replaceable, similar to the battery of mobile terminal which is mounted in the mobile terminal replaceably.

It is very convenient to mount and dismount the flash memory part.

Because the USB interface and the controller in the present invention are
20 standard-opened components, the controller can also connect with other parts which are needed to connected with a computer, such as the infrared-ray receiver as wireless transmission equipment and the seat of IC card.

Description of Figures

25 Fig. 1 is an exploded explanatory diagram showing one embodiment of the present invention;

Fig. 2 is a diagram showing the structure of the side of the device shown

in Fig. 1;

Fig. 3 is a diagram showing the structure of the front of the device shown in Fig. 1;

Fig. 4 is an exploded explanatory diagram showing another embodiment of the present invention;

Fig. 5 is a diagram showing the structure of the side of the device shown in Fig. 4;

Fig. 6 is a diagram showing the structure of the front of the device shown in Fig. 4;

Fig. 7 is an exploded explanatory diagram showing further embodiment of the present invention;

Fig. 8 is a diagram showing the structure of the side of the device shown in Fig. 7;

Fig. 9 is a diagram showing the structure of the front of the device shown in Fig. 7;

Fig. 10 is an exploded explanatory diagram showing still further embodiment of the present invention;

Fig. 11 is a block diagram showing the electrical connection of the present invention.

20

Mode of Carrying out the Invention

The present invention will be explained in detail with reference to the drawings and concrete embodiments.

As shown in Fig. 1-10, the present invention is an USB removable memory with replaceable storage medium for optional upgrade and extension of the storage capacity. It includes an USB connector 1, a controller 2 and a flash memory 3. Wherein, the USB connector 1 and the controller 2 are integrated as a memory

body 3. The flash memory 4 as the physically-independent storage component is attached to the body 3, and is electrically connected to the controller 2. The data transmission can be completed by using the standard interface protocol, such as the USB, I2C. The electrical connection are shown in Fig. 11. Therefore, the storage component can be replaced optionally, so as to meet the various requirements. For example, when the capacity of the flash memory 4 is not enough, the flash memory 4 can be replaced just with a larger one having larger capacity of storage, or the flash memory 4 can be replaced with a plurality of flash memory parts, while one USB connector 1 and one controller 2 are still used. In this way, not only the flexibility of the USB removable memory is improved in respect of extension of the storage capacity, but also the cost of the USB removable memory is largely reduced, so the resource of component is saved.

The concrete embodiment is as follows:

Refer to Fig. 1, 2 and 3, a dismountable back cover 5 is provided in the rear of the housing of the body 3 according to the present invention, which can be opened and closed. Specifically, the back cover 5 can be mounted on the body 3 by means of guide channel, and can slid on the guide channel, as shown in Fig. 1, 10. Certainly, the back cover 5 can be provided with elastic fastener such as clip and tenon which can fasten the back cover 5 onto the body 3. The body 3 is provided with a chamber for flash memory part 4, a flash memory part 4 is placed in the chamber, and the back cover 5 covers the chamber. The electrical connection 6 between the flash memory part 4 and the controller 2 is elastic tip-touch connection. The electrical connection 6 as shown in Fig. 10 is plug-in connection. When the flash memory part 4 is needed to replace, the whole procedure is the following: opening the back cover 5; then take out the flash memory part 4; finally put a new flash memory part 4 in the correct position in the chamber.

Furthermore, the body 3 is provided with write/read status control switch

7.

The flash memory part 4 is also integrated with the back cover 5. The flash memory part 4 is mounted on the body 3 by means of guide channel or fastener. The electrical connection 6 can be either the elastic tip-touch connection or
5 plug-in connection.

Another embodiment of the present invention is shown in Fig. 4, 5 and 6. In the embodiments, the flash memory part 4 is a self-housing independent part, whose housing can be completely separated from the body 3 and can be connected to the body 3 by means of the plug-in connection similar to the connection between
10 a plug and a plug socket. An electrical connection contact adapter is provided in the electrical connection section 6 of the flash memory 4 and controller 2.

In addition, another embodiment of the present invention is shown in Fig. 7, 8 and 9. In the embodiment, the flash memory part 4 is a self-housing independent part, whose housing can be completely separated from the body 3 and
15 can be connected to the body by means of elastic fastener. A elastic clasp 8 is formed on the housing of the flash memory part 4, and a notch is formed on the body 3. The elastic clasp is set into the notch in conjugation status. An electrical connection contact adapter is provided in the electrical connection section 6 of the flash memory 4 and controller 2.

20 Finally, it should be noted that above embodiments are used only to explain the present invention, but not to limit the present invention. In despite of the detailed description of the present invention with reference to above preferred embodiments, it should be understand that various modifications, changes or equivalent replacements can be made by those skilled in the art without
25 depart from the spirit and scope of the present invention, which should be covered in the append claims of this application.